

Super Slicer II

SUPER SLICER II

OVER 25 YEARS
OF FIELD-TESTED
KNOW-HOW

UNIFORM FEEDING

MINIMUM WASTE



Allows you to keep the leaves at feeding time that you worked so hard to preserve at baling time.

PATENTED SICKLE GUARD

FIELD-TESTED KNOW-HOW



Keeps the sickles close to the top guard ensuring a good cut rather than clumped hay.

MINIMUM WASTE

FULL BALE FEEDING CONTROL



Slices and Unrolls in feed bunks or fence line.

SELF LOADING

DOUBLE BALE CAPACITY



Lifts and loads two big bales, **One Man Operation.**

SUPER SLICER II SPECIFICATIONS

Frame	
Pickup Lift Cylinder	4" x 18"
Width	Transport: 8'6" Working: 9'10"
Height	9'
Length	12'4"
Min. Hydraulic Requirements	Dual Tractor Hydraulic Outlets 12-15 GPM Flow at 1800 PSI
Flow Controls	For Variable Speed of Sickle and Slats
Options	540 PTO Drive

DewEze reserves the right to make changes in designs and specifications without notice. For more information, contact your nearest DewEze dealer.



Two hydraulic orbit motors with two manual adjusted flow controls.



One spot easy string retrieval

DEWEZE®